



CITY OF MODESTO

Public Works Department
Environmental Compliance Section
1221 Sutter Ave., Modesto, CA 95351
Ph: (209) 577-6377 Fax: (209) 577-6290



PLAN CHECK REVIEW

For ECS Use Only

Project Number

Facility Name: _____

Facility Address: _____

City: _____ State: _____ Zip: _____

Primary Contact: _____ Ph: _____ Fax: _____

Owner: _____ Ph: _____ Fax: _____

Owner's Address: _____

City: _____ State _____ Zip: _____

Effluent Sampling: A separate effluent sampling chamber on grease interceptors is required. Grease interceptors and separated effluent sampling chambers must be in compliance with the current City of Modesto Standard Specifications - Chapter 5: Sanitary Sewer Design.

GREASE INTERCEPTOR Size: _____ Sampling Chamber Required: **Yes | No**

GREASE TRAP Size: _____ Waiver Approved by: _____ Date: _____
***For Waivers: Send waiver letter with conditions.*

NO GREASE CONTROL DEVICE NEEDED
 Received Conditional Waiver Waiver Approved by: _____ Date: _____
 Not Applicable to F.O.G. Program-No waiver needed ***For Waivers: Send waiver letter with conditions.*

PLAN RESUBMITTAL REQUIRED

Reason/Requirement: _____

Contacted On: _____ Plans Resubmitted On: _____

Plans Reviewed By: _____ Start Date: _____ Completion Date: _____

Plans Approved By: _____ Date: _____

Comments: _____



CITY OF MODESTO

Public Works Department
Environmental Compliance Section
1221 Sutter Ave., Modesto, CA 95351
Ph: (209) 577-6377 Fax: (209) 577-6290



PLAN REVIEW CHECKLIST

General Information

- Project Number
- Facility Name & Address
- Contact / Owner Information

Plan Check

- Interceptor Sizing in accordance with the current adopted California Uniform Plumbing Code.
- Verify the location of the interceptor.
 - Grease traps shall not be installed in the food preparation areas of the kitchens.
 - Grease interceptors shall be installed outside of the kitchen area in a location affording ease of maintenance and servicing.
- All restaurant wastewater and waste from floor drains, floor sinks, sinks, waste container wash racks, dishwashers, and garbage grinders, or like equipment shall be directed through a minimum seven hundred fifty (750) gallon gravity separation interceptor.
- All domestic wastewaters from restrooms, showers, drinking fountains, and condensate (i.e., ice melt, air conditioning) shall be kept separate from the restaurant wastewater until the restaurant wastewater has passed through all necessary pretreatment equipment, devices or monitoring stations.
- Verify that the sewer line is going from the interceptor to the City of Modesto sewer main.
- A diagram of the interceptor including the sample box with inlet and outlet lines.
- Sample box on the interceptor must have an inlet line approximately eight and one half inches (8.5") higher than the outlet line.